

# DYNASCAN



Model		PH-300EM	PH-400EM
Screen Diameter		300mm	400mm
		Fine Grain Ground Glass with Solid Cross Lines	
Electronic Protractor		Display Range : +/- 360 Degree, Abs/Inc, Zero Setting through Geometric Data Processor	
Magnification	Standard	10X	
	Optional	20X, 50X	20X, 50X, 100X
	Remarks	Lens mounted in turret (Maximum 3 Lens)	
Magnification Accuracy		Contour Illumination : +/- 0.05% , Surface Illumination : +/- 0.075%	
Work Stage Table Top Area		400 x 125mm with 1 T Slot	450 x 160mm with 1 T Slot
Measuring Range X-Y Axis		200 x 100mm	300 x 150mm
Resolution		0.001mm	
Focussing Distance		50mm	70mm
Measuring System		Built in Linear Scale	
Digital Readout		Geometric Data Processor	
Illumination System		Profile 1 Bulb : 150W 24V, surface 2 Bulbs : 250W 24V	
Power Supply		Single Phase AC 200 ~ 240V	
Mass		130kg	140kg
Optional Accessories		Rotary Table, Pair of V Blocks, Vertical Work Piece Holder, Pedestal Stand	

MEASURING INSTRUMENT TECHNOLOGY PTE LTD



TEL : 65 6275-6966 FAX: 65 6275-6977

EMAIL : sales@mit-sg.com

WEBSITE: <http://www.mit-sg.com>