

DYNASCAN



Model		PT-300EM	PT-400EX
Screen Diameter		300mm	400mm
		Fine Grain Ground Glass with Solid Cross Lines	
Electronic Protractor		Display Range : +/- 360 Degree, Abs/Inc, Zero Setting through Geometric Data Processor	
Magnification	Standard	10X	
	Optional	20X, 50X	20X, 50X, 100X
	Remarks	Lens mounted in turret (Maximum 3 Lens)	
Magnification Accuracy		Contour Illumination : +/- 0.05%, Surface Illumination : +/- 0.075%	
Work Stage Table Top Area		300 x 280mm	350 x 280mm
Measuring Range X-Y Axis		200 x 150mm	250 x 175mm
Resolution		0.001mm	
Maximum Workpiece Height		110mm	
Measuring System		Built in Linear Scale	
Digital Readout		Geometric Data Processor	
Illumination System		Profile 1 Bulb : 150W 24V, Surface 2 Bulbs : 250W 24V	
Power Supply		Single Phase AC 200 ~ 240V	
Mass		125kg	130kg
Optional Accessories		Inclinable Centres, V Blocks, Holder with Clamp, Pedestal Stand	

MEASURING INSTRUMENT TECHNOLOGY PTE LTD



TEL : 65 6275-6966 FAX: 65 6275-6977
EMAIL : sales@mit-sg.com
WEBSITE: <http://www.mit-sg.com>