

THREADMASTER

Screw Plug and Ring Gauges

FREE UKAS CERTIFICATES

ALL SCREW PLUGS GAUGES
ALL SPECIAL SCREW RINGS
ALL PLAIN PLUG GAUGES
ALL PLAIN RING GAUGES
ALL TAPER SCREW PLUG GAUGES
ALL TAPER SCREW RING GAUGES

COMMON INFORMATION

- NON-STANDARD GAUGE
- HARD CHROME PLATING/ TIN COATING/
CARBIDE COATING
- HANDLES WITH ADDITIONAL ENGRAVING



INFORMATION AVAILABLE FOR ORDERING *(All the gauges prices on application)*

METRIC-SCREW PLUG AND RING GAUGES ISO TO B.S. 3643
SCREW PLUG GAUGES CLASS 6H
SCREW RINGS AND CALIPERS CLASS 6g

WHITWORTH-SCREW PLUG AND RING AND CALIPER GAUGES TO B.S. 84
SCREW PLUG GAUGES MEDIUM
SCREW RINGS AND CALIPERS 3/4" AND BELOW GEN- MED U/P
SCREW RINGS AND CALIPERS OVER 3/4" GEN/MED

'G' SERIES-(FORMERLY BSPF) SCREW PLUG, RING AND CALIPER GAUGES TO B.S. 2779
SCREW RINGS AND CALIPERS CLASS 'A' OR CLASS 'B'

B.A.-SCREW PLUG, RING AND CALIPER GAUGES TO B.S. 93
SCREW PLUG GAUGES NORMAL
SCREW RINGS AND CALIPERS NORMAL U/P

U.N.E.F., U.N.F. AND U.N.C.-SCREW PLUG, RING AND CALIPER GAUGES ISO TO B.S. 1580, FEDERAL H.28
SCREW PLUG GAUGES CLASS 2B
SCREW RINGS AND CALIPERS CLASS 2A

AMERICAN-SCREW PLUG, RING AND CALIPER GAUGES TO FEDERAL H.28
ORDERS FOR THESE THREADS MUST STATE CLEARLY "AMERICAN STANDARD" OR "H.28" AND MUST SPECIFY THE CLASS OF FIT
UNLESS SPECIFICALLY REQUESTED NOT GO PLUG GAUGE MEMBERS WILL BE MANUFACTURED TO HI-ADDENDUM AND MINUS TOLERANCES

ALL GAUGES-MANUFACTURED TO B.S. 919 PARTS 1, 2 AND 3- PLEASE STATE WHETHER PART 2 GAUGES ARE REQUIRED TO GENERAL OR REFERENCE LIMITS WHEN ORDERING

SCREW PLUG GAUGES: STATE WHETHER STYLE A,D,E,F,G,H OR SINGLE-ENDED 'GO' PLUGS ARE REQUIRED
STYLE A- DOUBLE-ENDED SETTING PLUG FOR SCREW CALIPER GAUGES
STYLE D- DOUBLE-ENDED EFFECTIVE 'NOT GO' SCREW PLUG GAUGE
STYLE E- COMBINATION OF BOTH 'GO AND 'NOT GO' SCREW PLUG GAUGE
STYLE F- 'GO' SCREW PLUG GAUGE AND 'NOT GO' PLAIN CORE PLUG
STYLE G- 'GO' SCREW PLUG AND 'GO' PLAIN CORE PLUG GAUGE
STYLE H- 'NOT GO' SCREW PLUG AND 'NOT GO' PLAIN CORE PLUG GAUGE

PLAIN:

PLAIN DOUBLE-ENDED PLUGS WILL BE SUPPLIED TO B.S. 969: 1982 UNLESS OTHERWISE REQUESTED. IF THE GAUGE TOLERANCE IS NOT CONFIRMED ALL PLAIN SINGLE-ENDED GAUGES WILL HAVE THE FOLLOWING MINIMUM MANUFACTURING TOLERANCE:

UP TO AND INCLUDING 2.510" DIAMETER 0.0001"
OVER 2.510" DIAMETER UP TO 4.010" DIAMETER 0.0002"



MEASURING INSTRUMENT TECHNOLOGY PTE LTD



TEL : 65 6275-6966 FAX: 65 6275-6977
EMAIL : sales@mit-sg.com
WEBSITE: <http://www.mit-sg.com>